

FX-SMT™ Series Intelligent Single Gas Transmitter

Single gas transmitter ideal for hydrocarbon gases, oxygen content or toxic gases.



FX-SMT
(LEL or PPM)
(combustible)



FX-SMT



FX-SMTn



Optional Accessories

- ◆ Calibration Kit
- ◆ Local Alarm Relay Module (hydrocarbon version only)

The FX-SMT Series Transmitters are loaded with industry features. These transmitters come standard with non-intrusive calibration which eliminates the need to declassify hazardous areas and a user adjustable "calibration reminder" message, smart sensor replacement assemblies available for plug-in operation.

This single gas transmitter can be configured for the detection of hydrocarbons, AsH_3 , B_2H_6 , Cl_2 , ClO_2 , CO , F_2 , HCl , HCN , HF , H_2S , NH_3 , NO , NO_2 , O_2 , O_3 , PH_3 , SiH_4 , or SO_2 .

- ◆ Non-intrusive calibration via a magnetic wand eliminates the need to declassify hazardous areas
- ◆ User adjustable "calibration reminder"
- ◆ Pre-calibrated sensors for quick and easy plug-in operation
- ◆ Connect to Thermo controllers, PLC (Programmable Logic Controllers) or DCS (Distributive Control System)
- ◆ Industrial standard, 4 to 20 mA output
- ◆ Housed in a NEMA 4X, copper-free aluminum enclosure (weather & explosion proof)
- ◆ User friendly and simple to operate
- ◆ Economical

Product Specifications

Sensors

- ◆ Combustibles: catalytic compensated
- ◆ Electrochemical: AsH₃, B₂H₆, Cl₂, ClO₂, CO, F₂, HCl, HCN, HF,

H₂S, NH₃, NO, NO₂, O₂, O₃,

PH₃, SiH₄, or SO₂

Analog Output

4-20 mA

Relay Outputs (hydrocarbon only)

Optional Local Alarm Relay Module contains three SPDT (Form C) relays housed in a separate explosion-proof junction box. Each relay rated at 10A/30 VDC, 10A/250 VAC

Accuracy

±10% of reading

Repeatability

±5% of reading

Operating Temperature

-4°F to 113°F (-20°C to 45°C)

Humidity

0 to 95% RH, non-condensing

Alarms

Low/High Gas and Sensor Failure Indicator with visual LED

Display

1 x 16 character LCD

Alarm Delay

User selectable

Controls

- ◆ Four push-button switches to set the parameters of range, alarm setting, alarm delay, and alarm latching
- ◆ Magnetic switch for non-intrusive calibration

Power Consumption

- ◆ 4 watts at 24 VDC (combustible only), 3 wires
- ◆ 280 mW at 24 VDC (toxic/O₂), 2 wires

Input Power

10-28 VDC, loop-powered

Dimensions

6.2 in (158 mm) L x

4.6 in (117 mm) H x

10 in (254 mm) W

Weight

5 lbs (2.3 kg)

Case Materials

Aluminum - high impact, chemical, EMI & RFI resistant

FX-SMT Approvals

- ◆ UL Classified for Class I, Division 1, Groups B, C, & D (combustible version)
- ◆ FX-SMTn is rated for general purpose use only.

Response Time

- ◆ 90% in less than 60 seconds (except Combustibles, HCL, and HF)
- ◆ 90% in less than 70 seconds (HCL)
- ◆ 90% in less than 90 seconds (HF)
- ◆ 90% in less than 30 seconds (Combustibles)

Warranty

One year (materials and workmanship)

Gas	Sensor Type	Formula	Standard Range
Ammonia	Electrochemical	NH ₃	0 to 100 ppm in 1 ppm increments
Arsine		AsH ₃	0 to 1.00 ppm in 0.01 ppm increments
Carbon monoxide		CO	0 to 500 ppm in 1 ppm increments
Chlorine		Cl ₂	0 to 10.0 ppm in 0.1 ppm increments
Chlorine dioxide		ClO ₂	0 to 2.00 ppm in 0.01 ppm increments
Diborane		B ₂ H ₆	0 to 1.00 ppm in 0.01 ppm increments
Fluorine		F ₂	0 to 10.0 ppm in 0.1 ppm increments
Combustible	Catalytic		0 to 100% LEL in 1% LEL
Hydrogen chloride	Electrochemical	HCl	0 to 30.0 ppm in 0.1 ppm increments
Hydrogen cyanide		HCN	0 to 50.0 ppm in 0.1 ppm increments
Hydrogen fluoride		HF	0 to 10.0 ppm in 0.1 ppm increments
Hydrogen sulfide		H ₂ S	0 to 100 ppm in 1 ppm increments
Nitric oxide		NO	0 to 100 ppm in 1 ppm increments
Nitrogen dioxide		NO ₂	0 to 20.0 ppm in 0.1 ppm increments
Oxygen		O ₂	0 to 30.0% Vol. in 0.1% Vol.
Ozone		O ₃	0 to 1.00 ppm in 0.01 ppm increments
Phosphine		PH ₃	0 to 1.00 ppm in 0.01 ppm increments
Silane		SiH ₄	0 to 20.0 ppm in 0.1 ppm increments
Sulfur dioxide		SO ₂	0 to 20.0 ppm in 0.1 ppm increments



This specification sheet is for informational purposes only and is subject to change without notice. Thermo makes no warranties, expressed or implied, in this product summary. © 2007 Thermo Fisher Scientific Inc. All rights reserved Thermo Fisher Scientific Inc.

Lit_FXSMTAQI_2/08

Environmental Instruments
Industrial Hygiene Instruments

27 Forge Parkway
Franklin, MA
02038 USA

+1 (866) 282-0430
+1 (508) 520-1460 fax

Takkebijsters 1
Breda, BL 4817
The Netherlands

+33 (0) 76 5879888
+33 (0) 76 5816520 fax

www.thermo.com/ih

Thermo
SCIENTIFIC