

Multi-Channel Gas Monitoring System, SafeTNet 210™ & 410™

Wall mounted, continuous monitoring control system



SafeTNet 210
1 or 2 Channels



SafeTNet 410
1 to 4 Channels



Key Features

- All functions are fully programmable through dip & push button switches
- Generic programming design allows configuration to any standard 4 to 20 mA detector head
- Common fault alarm relay
- Digital display (3 digits)
- One-person calibration
- Housed in NEMA 4X fiberglass enclosure
- 98 dB loud external buzzer

The Thermo Scientific Multi-Channel Gas Monitoring System, SafeTNet 210 and the SafeTNet 410 are microprocessor-based controllers designed to accept one to two (STN210) or one to four (STN410) combustible, oxygen, and/or toxic gas transmitters.

Standard features include: digital readout display, LED alarm indication, 4 to 20 mA output, individual low and high alarms, and a common fault alarm relay.

Applications Include:

- Waste Treatment plants
- Water Treatment plants
- Petrochemical refineries
- Pulp & paper mills
- Steel plants
- Mining & Tunneling operations
- Boiler plants
- Parking Garages
- Equipment Shelters

Multi-Channel Gas Monitoring System, SafeTNet 210™ & 410™

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

Product Specifications

Ranges	Each channel individually adjustable to 999 (decimal may be set in any position); Reads % LEL, PPM or % Vol.		
Inputs	4 to 20 mA inputs; Source type - 2 or 3 wire		
Transmitters	For use with combustible, oxygen & toxic gas detector heads		
Analog Output	One 4 to 20 mA source for each channel (1000 Ω maximum at 24 Vdc input)		
Relay Output	Individual low (Form C) and high (Form A or B) for each channel; programmable for latching/non-latching, energized/de-energized. Common fault (Form A or B); normally energized, programmable for latching/non-latching. Each relay rated at 10A/125 VAC		
Operating Temp.	-4 °F to 113 °F (-20 °C to 45 °C)		
Humidity	0 to 95% RH, non-condensing		
Area Classification	Non-hazardous locations		
Low Alarm	Independently adjustable from "Off" to full scale/audible & visual indication/can be activated for rising & falling level		
High Alarm	Independently adjustable from "Off" to full scale/audible & visual indication/can be activated for rising & falling level		
Calibration Time-out	Programmable, to 99 min. (may be disabled)		
Alarm Delay	Programmable, to 30 sec. (may be disabled)		
Audible Alarm	98 dB		
Programmable	♦ range	♦ calibration time-out	♦ alarm onset delay
	♦ alarm levels	♦ factory setting	♦ buzzer enable/disable
	♦ gas units	♦ one to two channel operation	♦ decimal place
Input Power	100/130 VAC 50/60 HZ, 200/260 VAC 50/60 Hz, 18 to 30 Vdc nominal - for use with battery back-up (optional)		
Current Consumption			
<i>Safe T Net 210:</i>	0.4 Amp fused at 2.0 Amp, Approximately 8 lbs. (3.75 kg)		
<i>Safe T Net 410:</i>	1.3 Amp fused at 2.0 Amp, Approximately 15.5 lbs. (7 kg)		
Physical Dimensions			
<i>Safe T Net 210:</i>	6.30" (160mm) L x 12.9" (328mm) H x 11" (280mm) W		
<i>Safe T Net 410:</i>	8.31" (211mm) L x 14.55" (370mm) H x 13.25" (337mm) W		
Case Material	NEMA 4X molded fiberglass polyester		
Approvals	UL Classified and CSA Certified for non-hazardous locations		
Warranty	One year (materials and workmanship)		

A wide range of transmitters are available:



Standard Transmitter



FX-SMT (LEL) (combustible)



FX-SMT (oxygen/toxic)



FX-IR



Sample-Draw Transmitter

This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. © 2009 Thermo Fisher Scientific, Inc. All rights reserved Thermo Fisher Scientific, Inc.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

Lit_STN210410AQL_08/09

**Environmental
Instruments Division**
Air Quality Instruments

27 Forge Parkway
Franklin, MA 02038 USA

(866) 282-0430
(508) 520-0430
(508) 520-1460 fax

www.thermo.com/ih

Thermo
SCIENTIFIC