

# Thermo Scientific identiFINDER™

Isotope Identifier

The Thermo Scientific identiFINDER™s are a family of compact and lightweight instruments for finding and identifying radionuclides. The integrated display and straightforward three push-button operation ensures ease-of-use in the field. The accessories supplied with every identiFINDER ensure that the field user can easily reach-back to the experts with useful data, should the need arise.



The Thermo Scientific identiFINDER is a user-friendly instrument that identifies man-made and natural radionuclides and combines high sensitivity with a wide dose rate range. The instrument has a dual purpose design to facilitate locating missing or offending sources and then identifying the source via its gamma spectrometry and nuclide identification capability.

The identiFINDER is a complete digital gamma spectroscopy and dose rate system. It integrates multi-channel analyzer, amplifier, high voltage power supply, and memory with an integral scintillation and GM detector. The identiFINDER is ideally suited for homeland security, industrial, medical, nuclear power generation and nuclear fuel cycle applications.

The identiFINDER also is available as an optional LaBR version, providing high-resolution spectroscopy at room

temperature. This version delivers laboratory-type performance in a lightweight, hand-held device, enabling improved results for difficult identifications.

### Features

- Top-of-the-line Ultra model available with patented pulsed LED stabilization and LTI deconvolution which no longer requires a built-in source for precise stabilization ( $\pm 0.5\%$  typical peak shift accuracy)
- Supplied with larger, more sensitive NaI(Tl) gamma detectors
- New, faster (5 to 10 x quicker identification) and lower power (longer battery life) electronics
- New, more rugged and ergonomic housing for easier use in the field
- Optional neutron detection now 50% more sensitive due to new  $^3\text{He}$  detector



Scope of supply — main components of the identiFINDER

## Thermo Scientific identiFINDER

Features	
Functions	Nuclide identification, spectrum analysis, dose rate calculation, total dose display, source finding
Integrated Electronics	Multi-Channel-Analyzer, PMT preamplifier, spectroscopy amplifier, power supply Standard Instruments: identiFINDER-NG+ with 35.5 mm x 50.8 mm (1.4 in x 2 in) NaI & GM detectors identiFINDER-NGH+ with 35.5 mm x 50.8 mm (1.4 in x 2 in) NaI, <sup>3</sup> He & GM detectors identiFINDER-NG Ultra with 35.5 mm x 50.8 mm (1.4 in x 2 in) NaI & GM detectors identiFINDER-NGH Ultra with 35.5 mm x 50.8 mm (1.4 in x 2 in) NaI, <sup>3</sup> He & GM detectors Specials (-L versions): with 30.5 mm x 35.5 mm (1.2 in x 1.4 in) LaBr with a resolution of <3.3% at 662 keV Watertight (-U versions): up to 1 atm (10 m or 33 ft) immersion Telescopic (-X versions): with ~1.2 m to 2.4 m (~4 ft to 8 ft) extension Safeguards: with 25.4 mm x 25.4 mm (1 in x 1 in) NaI (TI) tungsten shielded detector and specialized SNM firmware
Stabilization	In the non-Ultra models, a built-in <sup>137</sup> Cs reference source (<15 nCi/500 Bq) is used for online stabilization and in-situ calibration without user interaction. With either stabilization method this special identiFINDER feature allows operation over temperatures between -20°C and +55°C (-4°F and +122°F). The Ultra provides the user with the benefits of LED stabilization technology with or without a small <sup>3</sup> nCi <sup>137</sup> Cs source, as preferred for implementation and transportation.
Software	The identiFINDER provides for easy storage of up to 100 spectra and rapid transfer to a PC for reach-back and/or qualitative in-situ analysis with the software supplied.

**User Selectable Nuclide Library** There are 74 reference spectra of radionuclides stored in six libraries: Nuclear, Industrial, Medical, U.S. Customs Service, OSI (On Site Inspection by IAEA officials), and Security. All sub-libraries except OSI can be edited by adding or deleting specific nuclides from the list. Ten reference spectra can be measured by the user and added to the predefined library spectra. Identification is done by a template-matching correlation procedure.

Physical Dimensions	
Weight	1250 g (2.75 lb) with 35.5 mm x 50.8 mm (1.4 in x 2 in) NaI and batteries
Temperature Range	-20°C to +55°C (-4°F to +122°F)
Protection	Water proof, dust tight
Protection Class	IP 54
Battery Life	10-12 hours; common batteries can also be used (i.e., emergency situations)
Dimensions	248.92 mm x 94 mm x 76.2 mm (9.8 in x 3.7 in x 3 in)

Spectrometry System Specifications	
HV-Bias	200 V to 1275 V automatically set to suit individual detector
Shaping Type	Digital filter
INL, Top 99%	<0.05%
DNL, Top 99%	<0.1%
Spectrum Length	1024 channels
Pileup Rejection	<100 nS, pulse pair res.
Throughput Rate	>100,000 cps
Input Rate	>350,000 cps
Spectrum Memory	100 spectra at 1024 channels
Real Time Presets	1 s to 1,000,000 s
Live Time Presets	1 s to 1,000,000 s

Dose/ Dose Measurement Specifications	
Sensitivity	>10,000 cps/mrem for 35.5 mm x 50.8 mm (1.4 in x 2 in) NaI (TI) detector
Dose-rate Range	1 µrem/h to 100 rem/h max dose-rate equivalent to max dose-rate of NAI
Dose Range	10 µrem to 100 rem
Energy Range	NaI: 15 keV to 3.0 MeV; GM: 60 keV to 1.6 MeV
Alarm Levels	Gamma: Four preset levels
Neutron	Separate neutron alarms for <sup>3</sup> He model, with blue indicator lamp



Front view of the identiFINDER with

1. Battery compartment lock
2. ON/OFF button
3. Blue LED (neutron alarm)
4. Selection buttons
5. Command line
6. Red LED (gamma alarm)
7. Internal GM tube
8. Internal <sup>3</sup>He tube (neutron detection)
9. Internal NaI(Tl) scintillation detector

© 2008 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Results may vary under different operating conditions. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representatives for details. Literature Code RMP.4004.A0408

27 Forge Parkway  
Franklin, MA  
02038 USA  
+1 (800) 274-4212  
+1 (508) 520-2815 fax

Bath Road, Beenham  
Reading, Berkshire  
RG7 5PR United Kingdom  
+44 (0)160 654 8170  
+44 (0)160 654 8145 fax

Frauenauracher Straße 96  
D91056 Erlangen,  
Germany  
+49 (0) 208 82 4930  
+49 (0) 208 85 2320 fax

[www.thermo.com/rmp](http://www.thermo.com/rmp)

**Thermo**  
SCIENTIFIC