

## Thermo Scientific Hydrogen Sulfide and Sulfur Dioxide Analyzer, Model 450i


Pulsed fluorescence gas analyzer



### Key Features

- Pulsed excitation and intensity stabilization
- Reflective bandpass filters
- Temperature stabilization reaction chamber
- Stable, long-life UV source
- Superior zero stability

The Thermo Scientific Hydrogen Sulfide and Sulfur Dioxide Analyzer, Model 450i utilizes pulsed fluorescence technology. The Model 450i H<sub>2</sub>S and SO<sub>2</sub> analyzer operates on the principle that H<sub>2</sub>S can be converted to SO<sub>2</sub>. As the SO<sub>2</sub> molecules absorb ultraviolet (UV) light and become excited at one wavelength, the molecules then decay to a lower energy state emitting UV light at a different wavelength. Specifically,



The pulsing of the U.V. source lamp serves to increase the optical intensity whereby a greater U.V. energy throughput and lower detectable SO<sub>2</sub> concentration are realized. Reflective bandpass filters, as compared to commonly used transmission filters, are less

subject to photochemical degradation and are more selective in wavelength isolation. This results in both increased detection specificity and long term stability.

This state-of-the-art gas analyzer also offers features such as an ethernet port as well as flash memory for increased data storage. Ethernet connectivity provides efficient remote access, allowing the user to download measurement information directly from the instrument without having to be on-site.

You can easily program short cut-keys to allow you to jump directly to frequently accessed functions, menus or screens. The larger interface screen can display up to five lines of measurement information while primary screen remains visible.

# Product Specifications

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

## Hydrogen Sulfide and Sulfur Dioxide Analyzer, Model 450i

<b>Preset Ranges</b>	0-0.05, 0.1, 0.2, 0.5, 1, 2, 5, and 10 ppm 0-0.2, 0.5, 1, 2, 5, 10, 20, and 25 mg/m <sup>3</sup>				
<b>Extended Ranges</b>	0-0.5, 1, 2, 5, 10, 20, 50 and 100 ppm 0-2, 5, 10, 20, 50, 100, 200, and 250 mg/m <sup>3</sup>				
<b>Custom Ranges</b>	0-0.05 to 100 ppm 0-0.2 to 250 mg/m <sup>3</sup>				
<b>Zero Noise</b>	1.0 ppb	Manual H <sub>2</sub> S or CS	3.0 ppb	Auto	(10 second averaging time)
	0.5 ppb		1.5 ppb		(60 second averaging time)
	0.25 ppb		0.75 ppb		(300 second averaging time)
<b>Lower Detectable Limit</b>	2.0 ppb	Manual H <sub>2</sub> S or CS	6.0 ppb	Auto	(10 second averaging time)
	1.0 ppb		3.0 ppb		(60 second averaging time)
	0.5 ppb		1.5 ppb		(300 second averaging time)
<b>Zero Drift (24 hour)</b>	Less than 1 ppb				
<b>Span Drift (24 hour)</b>	+/-1% Full Scale				
<b>Response Time</b>	80 seconds (10 second average time) 110 seconds (60 second average time) 320 seconds (300 second average time)				
<b>Precision</b>	1% of reading or 1 ppb (whichever is greater)				
<b>Linearity</b>	+/-1% full scale				
<b>Sample Flow Rate</b>	1.0 liter/min.				
<b>Converter Efficiency</b>	> 80% H <sub>2</sub> S to SO <sub>2</sub> . Note: Various other Sulfur compounds can be converted at varying %				
<b>Operating Temperature</b>	20°C - 30°C				
<b>Power Requirements</b>	100 VAC, 115 VAC, 220-240 VAC +/-10% @ 300W				
<b>Size and Weight</b>	16.75"(W) x 8.62"(H) x 23"(D), 48 lbs. (21.8 kg)				
<b>Outputs</b>	Selectable Voltage, RS232/RS485, TCP/IP, 10 Status Relays, and Power Fail Indication (standard). 0-20 or 4-20 mA Isolated Current Output (optional)				
<b>Inputs</b>	16 Digital Inputs (standard), 8 0-10vdc Analog Inputs (optional)				
<b>Available Options</b>	Teflon particulate filter, Rack mounts, Rear extenders				

## Ordering Information

### Model 450i H<sub>2</sub>S/SO<sub>2</sub> Analyzer

Choose from the following configurations/options to customize your own Model 450i

#### 1. Voltage options:

A = 115 Vac 50/60 Hz  
B = 220 Vac 50/60 Hz  
J = 100 Vac 50/60 Hz

#### 2. Internal zero /span:

N = No zero / span assembly  
Z = Internal zero / span assembly  
P = Internal permeation span source with zero/span assembly

#### 3. Sample Handling:

S = Standard  
E = External Converter Setup (no converter supplied)  
H = Selective SO<sub>2</sub> Scrubber (Continuous H<sub>2</sub>S Analysis only)

#### 4. Optional I/O:

A = No optional I/O (standard)  
C = 0-20, 4-20mA current output - 6 channels, 0-10v analog input - 8 channels

#### 5. Mounting hardware:

A = Bench mounting (standard)  
B = Ears & handles, EIA  
C = Ears & handles, retrofit

Your Order Code: 450i - \_ \_ \_ \_ \_

© 2009 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries.

This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. Not all products are available in all countries. Please consult your local sales representative for details.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

Lit\_450iAQI\_10/09

#### Air Quality Instruments

27 Forge Parkway  
Franklin, MA 02038 USA

(866) 282-0430  
(508) 520-0430  
(508) 520-1460 fax

[www.thermo.com/air](http://www.thermo.com/air)

**Thermo**  
SCIENTIFIC