


At the heart of every Thermo Scientific CAHN C-33 Microbalance is a symmetrical, lightweight alloy beam, coupled to a rugged platinum taut-band suspension. This allows for a unique combination of stability, sensitivity and durability.

Thermo Scientific CAHN® C-33

Single Pan, Economical Microbalance



Typical application fields:

- Pharmaceutical
- Biotechnology
- Chemical Industry
- Semiconductor

Main Features:

- Convenient micro-weighing up to 250 mg tare range
- Portable – no balance table required
- System can take physical shocks
- No need for temperature-controlled environment

Single Pan, Economical Microbalance

The Thermo Scientific CAHN C-33 Microbalance enables microweighing at a very affordable price. The Thermo Scientific CAHN C-33 has only one hang-down position and there is no counter-weight pan. With a tare range of up to 250 mg, the CAHN C-33 can handle almost any container, making it more convenient to weigh.

The CAHN C-33 is ideal for weighing biological material, filters, standards for serial dilutions, and precious chemicals, all of which usually require a microbalance.

The CAHN C-33 is extremely stable and can be used on a normal lab bench and does not require a temperature-controlled environment.

Thermo Scientific CAHN C-33 Specifications

The CAHN C-33 is ideal for weighing biological material, filters, standards for serial dilutions, all which require a microbalance.

	Specification	Benefit
Capacity	250 mg	Weigh a variety of samples
Weigh Range (1 µg precision)	200 mg	Quick weighing over the entire range
Readability	1.0 µg	High sensitivity
Reproducibility	1.0 µg	Great precision, economical
Linearity	1.0 µg	Readings you can trust
Tare Range	250 mg	Can handle almost any container
Response Time	10 sec	Quick and stable reading
Output	RS232	Bi-directional RS232
Pan Size	Up to 60 mm	Large sample sizes
Housing Size (cm)	41.5 x 23 x 27.5	Fits easily on any benchtop
Net Weight	8 Kg	Light weight and portable
Power	100 to 240 VAC	

Above data generated under optimal/controlled circumstances.

Thermo Scientific CAHN C-33 Ordering information

C-33	Description of Balance and Accessories
13633-01	C-33 Microbalance, 250 mg capacity, single weighing range. Power selection for 100, 120, 220, 240 V, 50/60 Hz
01269-01	Ionizing Unit, eliminates static charge on balance surfaces and samples, 12 months of useful life
10407-01	Microbalance Accessory Pack for use with C-34 & C-35. Contains micro-spatula, 19 mm open & 22 mm platform stirrups, (100) 12 mm Al pans, (20) 25 mm Al pans, non-magnetic forceps, and 200 mg Class 1.1 calibration weight
02027-01	Anti-Static Solution, 6 oz. bottle, eliminates static charge on balance surfaces
01577-01	Forceps, non-magnetic stainless steel, for handling Class 1.1 weights and filter samples
10406-01	Spatula, vibrating
12555-01	Interface Cable, RS232, null modem
01427-01	Weight, 100 mg, flat, Class 1.1
01540-01	Weight, 200 mg, flat, Class 1.1
06137-01	Weight, 1 g, flat, Class 1
02888-01	Tare Set, 1-500 mg Includes: (1) 1 mg, (2) 2 mg, (1) 5 mg, (1) 10 mg, (2) 20 mg, (1) 50 mg, (1) 100 mg, (2) 200 mg, (2) 500 mg, tare weights
01187-01	Pan, Al, 12 mm, each ~ 17 mg, 20/pk
01187-02	Pan, Al, 12 mm, each ~ 17 mg, 100/pk
01568-02	Pan, Al, 25 mm, each ~ 35 mg, 20/pk
02034-01	Weighing Cup, Teflon, ~ 51 mg, 15 x 11 mm
02034-48	Weighing Cup, Teflon, 1.8 mL, ~ 60 mg, 48/pk
14076-01	Boat, Al, 130 mg, 10/pk
01129-01	Stirrup, open, 19 x 19 x 9 mm, 8 mg
09353-02	Stirrup, platform, 22 x 41 x 20 mm
04741-01	Stirrup, platform, 60 x 20 x 38 mm

© 2007/10 Thermo Fisher Scientific Inc. · All rights reserved · CAHN is a trademark of Thermo Fisher Scientific · 623-8032
 US PI-MC-623-8032-DB07/08 · This document is for informational purposes only and is subject to change without notice. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Process Instruments

Benelux

Tel. +31 (0) 76 579 55 55
 info.mc.nl@thermofisher.com

China

Tel. +86 (21) 68 65 45 88
 info.mc.china@thermofisher.com

France

Tel. +33 (0) 1 60 92 48 00
 info.mc.fr@thermofisher.com

India

Tel. +91 (22) 27 78 11 01
 info.mc.in@thermofisher.com

United Kingdom

Tel. +44 (0) 1785 82 52 00
 info.mc.uk@thermofisher.com

USA

Tel. 603 436 9444
 info.mc.us@thermofisher.com

International/Germany

Dieselstr. 4
 76227 Karlsruhe
 Tel. +49 (0) 721 4 09 44 44
 info.mc.de@thermofisher.com

www.thermo.com/mc

Thermo
 SCIENTIFIC