

Thermo Scientific Forma[®] Value Laboratory Refrigerators and Freezers

Cost-effective solutions for non-critical storage



Our cold storage products span refrigerators, freezers and refrigerator/freezer combination units to provide versatile, cost-effective storage for non-critical laboratory applications.

- **Easy Cleaning:** Rugged, white acrylic exteriors; seamless, easy-to-clean interiors
- **Economical:** Foam-in-place insulation ensures consistent performance and low operating costs
- **Environmentally-friendly:** CFC-free refrigerants and insulation

Capacity

- Refrigerator capacities from 7 to 43 cu. ft.
- Freezer capacities from 5 to 30 cu. ft.

Selection

- Combination, undercounter, single and double-door models

Adjustable Temperature Control

- Refrigerator temperature range +2°C to +8°C or +2°C to +10°C (factory pre-set to +4°C)
- Freezer temperature range -12°C to -20°C (factory pre-set to -20°C)

Thermo Scientific Forma Value Laboratory Refrigerators and Freezers

Forma Value refrigerators, freezers and combination units meet a wide range of temperature, space and capacity requirements for non-critical sample storage.



Specifications and Ordering Information

Forma Value Laboratory Refrigerators

Factory preset +4°C

Cat. No.	Volume cu.ft. (Liters)	Voltage/Hz	Temperature Range	Shelves Supplied	Door Lock	Interior Dimensions H x W x D, inches (mm)	Exterior Dimensions H x W x D, inches (mm)	Ship Weight lbs (kg)	Noise Level (dBA)	Heat Dissipation (BTU/h)
FRLR065A	7 (184)	115/60/1 phase	+2°C to +10°C	3	standard	27 x 21 x 18 (686 x 521 x 458)	34 x 24 x 24 (867 x 610 x 605)	116 (52)	35	204
FRLR1611A	15 (411)	115/60/1 phase	+2°C to +10°C	3	standard	52 x 27 x 18 (1308 x 686 x 457)	65 x 32 x 28 (1656 x 813 x 711)	235 (107)	45	295
FRLR2111A	21 (586)	115/60/1 phase	+2°C to +10°C	4	standard	57 x 27 x 24 (1448 x 686 x 597)	70 x 32 x 30 (1783 X 813 x 769)	250 (113)	45	295
FRLR294A	29 (827)	115/60/1 phase	+2°C to +10°C	4	standard	65 x 32 x 26 (1654 x 813 x 660)	76 x 35 x 34 (1935 x 889 x 861)	350 (159)	45	903
FRLR314A	31 (881)	115/60/1 phase	+2°C to +10°C	4	none	63 x 32 x 24 (1607 x 813 x 610)	76 x 36 x 32 (1937 x 923 x 806)	350 (159)	45	1138
FRLR4304A	43 (1218)	115/60/1 phase	+2°C to +10°C	8	none	57 x 49 x 27 (1448 x 1245 x 673)	76 x 53 x 32 (1930 x 1346 x 813)	645 (293)	73	2355

Forma Value Laboratory Freezers

Factory preset -20°C

Cat. No.	Volume cu.ft. (Liters)	Voltage/Hz	Temperature Range	Shelves Supplied	Door Lock	Interior Dimensions H x W x D, inches (mm)	Exterior Dimensions H x W x D, inches (mm)	Ship Weight lbs (kg)	Noise Level (dBA)	Heat Dissipation (BTU/h)
FREF417A	5 (141)	115/60/1 phase	-12°C to -20°C	2	none	29 x 19 x 20 (737 x 476 x 495)	34 x 21 x 27 (851 x 540 x 673)	84 (38)	28	–
FREF065A	7 (184)	115/60/1 phase	-12°C to -20°C	3	standard	27 x 21 x 18 (686 x 521 x 458)	34 x 24 x 24 (867 x 610 x 605)	123 (56)	28	221
FREF1617A	17 (490)	115/60/1 phase	-12°C to -20°C	3	standard	52 x 27 x 22 (1308 x 686 x 546)	65 x 32 x 28 (1656 x 813 x 711)	235 (107)	45	412
FREF2117A	21 (586)	115/60/1 phase	-12°C to -20°C	4	standard	57 x 27 x 24 (1448 x 686 x 597)	70 x 32 x 30 (1783 x 813 x 768)	250 (114)	45	412
FRLF2918A	30 (861)	115/60/1 phase	-12°C to -20°C	4	standard	64 x 32 x 26 (1613 x 813 x 660)	76 x 36 x 34 (1918 x 902 x 863)	350 (159)	45	1978

Forma Value Laboratory Refrigerator/Freezer Combinations

Factory preset +4°C (Refrigerator), Factory preset -20°C (Freezer)

Cat. No.	Volume cu.ft. (Liters)	Voltage/Hz	Temperature Range	Shelves Supplied	Door Lock	Interior Dimensions H x W x D, inches (mm)	Exterior Dimensions H x W x D, inches (mm)	Ship Weight lbs (kg)	Noise Level (dBA)	Heat Dissipation (BTU/h)
FRCRF192A	19 (522)	115/60/1 phase	+2°C to +10°C/ -12°C to -20°C	3	none	39 x 26 x 24 (991 x 660 x 610) ¹ 17 x 25 x 22 (438 x 641 x 552) ²	67 x 30 x 31 (1708 x 753 x 784)	225 (102)	35	605
FRCRF252A	25 (697)	115/60/1 phase	+1°C to +7°C/ -14°C to -21°C	6	none	38 x 32 x 25 (960 x 813 x 622) ¹ 19 x 31 x 21 (476 x 787 x 521) ²	69 x 36 x 34 (1742 x 914 x 854)	142 (64)	45	605

¹ Refrigerator compartment, ² Freezer compartment

Specified interior volumes are nominal, and usable capacities may be offset by shelves, drawers, blower coils or cabinet protrusions.

Refrigerator and/or freezer performance may be affected by ambient temperature and humidity conditions, sample loading preferences, and frequency of door openings.

Plug Guide

Model Code	Plug	Required Receptacle	NEMA Plug	Receptacle
P1			5-15P	5-15R

North America: USA/Canada +1 866 984 3766

Europe: Austria +43 1 801 40 0, Belgium +32 2 482 30 30, Finland +358 9 329 100, France +33 2 2803 2000, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 95059 1, Netherlands +31 76 571 4440, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203

Asia: China +86 21 6885 4588 or +86 10 5850 3588, India +91 22 5542 9494, Japan +81 45 453 9220, Other Asian countries +852 2885 4613

Countries not listed: +49 6184 90 6940 or +33 2 2803 2000

www.thermo.com/cold

© 2007 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

DS-LEFOVGP-0907

Thermo
SCIENTIFIC