

**MATERIAL SAFETY DATA SHEET**

|   |                        |   |
|---|------------------------|---|
| 7998 Georgetown Rd.<br>Suite 1000<br>Indianapolis, IN 46268 | DOCUMENT TITLE         | <b>COLOR-RICH CARBOXYLATE MODIFIED<br/>POLYSTYRENE</b>  |
|   | DOCUMENT NO:           | 13200750020250<br>PREFIX: 13,14,15,18,19,20,23,39,40,41,49,53,54,57<br>62,63,73,75,76,77,83,84,87,88,93,94,95 |
|   | DCR NO: 5610           | REVISION: C   |
| Page 1 of 3   | EFFECTIVE DATE: JUL 05 |   |

**SECTION I: IDENTIFICATION**

Seradyn, Inc.  
7998 Georgetown Rd. Suite 1000  
Indianapolis, Indiana 46268

Telephone Number: (317) 610-3800  
Fax: (317) 610-0018  
email: www.seradyn.com

| <u>Product/Common Name</u>                  | <u>Formula</u> | <u>Hazardous</u> |
|---|----------------|------------------|
| Color-Rich Carboxylate Modified Polystyrene | Mixture        | No               |

Date Revised: 7/8/2005

**SECTION II: HAZARDOUS INGREDIENTS**

Latex particles are supplied in aqueous suspensions of various concentrations ranging from 2.5% to over 40%. The ingredient(s) listed in this section describe only the solids.

|  | <u>APPROX. %</u> | <u>HAZARDOUS</u> |
|--|------------------|------------------|
| Proprietary Carboxylated Styrene Polymer | 100% w/w         | No               |

Pursuant to OSHA Hazard Communication Standard 29CFR 1910.1200, the above product is not considered to contain hazardous materials. Where proprietary ingredient shows, the identity may be made available as provided in this standard.

**SECTION III: PHYSICAL DATA**

|                      |  |
|----------------------|--|
| Boiling Point:       | 212F, 100C   |
| Vapor Pressure:      | 17.5 mmHg @ 20C                                    |
| Vapor Density:       | 0.624 @ 80F  |
| Solubility in Water: | Emulsion   |
| Specific Gravity:    | 0.980-1.040  |
| Appearance:          | Colors vary, depending on customer's specification |
| Odor:                | Slight odor  |

The physical data listed is for a series of latexes. For specific properties on any given latex see the product bulletin.

# Material Safety Data Sheet

|             |                 |   |
|-------------|-----------------|---|
| DCR: 5610   | DOCUMENT TITLE: | Color-Rich Carboxylate-Modified Polystyrene |
| REVISION: C | DOCUMENT NO:    | 13200750020250                              |
| Page 2 of 3 |                 | JUL 05                                      |

## SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable  
Flammable Limits: Not Applicable  
Extinguishing Media: Water fog - dried resin only.  
Fire and Explosion Hazards: The dried resin is combustible, similar to wood. Burning dry resin emits dense, black smoke. As latex, material is not combustible.  
Fire Fighting Equipment: Wear positive pressure self-contained breathing apparatus.

---

## SECTION V: REACTIVITY DATA

Stability: (Conditions to avoid) May coagulate if frozen at 32°F, 0°C or below. Dried resin is combustible.  
Incompatibilities: (Specific materials to avoid) Addition of chemicals may cause coagulation.  
Hazardous Combustion or Decomposition Products: If burned, produces a dense black smoke and noxious gases (carbon monoxide and hydrocarbons).  
Hazardous Polymerization: Will not occur.

---

## SECTION VI: HEALTH HAZARDS

This product is not considered to present a health hazard when handled using standard laboratory practices and general hygiene measures, i.e. wash hands thoroughly after handling.

---

## SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Contain spill with absorbent material. Wash and then dispose of absorbent material in an appropriate container. This product may contain < 0.1% sodium azide as a preservative (see product bulletin for specific properties). Sodium Azide can react with copper or lead plumbing to form highly explosive metal azides. Upon disposal, flush with a large volume of water to prevent azide build-up. Sodium Azide may be harmful if swallowed. In the event of oral exposure, and person is conscious, rinse mouth out with copious amounts of water. In all cases, immediately contact a physician.

---

## SECTION VIII: SPECIAL PRECAUTIONS

Store at temperatures between 40°F (4°C) and 110°F (43°C). Material may develop bacteria odor on long-term storage.

# Material Safety Data Sheet

|             |                 |   |
|-------------|-----------------|---|
| DCR: 5610   | DOCUMENT TITLE: | Color-Rich Carboxylate-Modified Polystyrene |
| REVISION: C | DOCUMENT NO:    | 13200750020250                              |
| Page 3 of 3 |                 | JUL 05                                      |

## SECTION IX: ADDITIONAL COMMENTS

The above information is believed to be correct, does not purport to be all-inclusive, and is for use only as a guide. Information provided is based on current knowledge, and is given to provide for the safe use of this product.

Employers should use this information only as a supplement to other information gathered by them and make independent judgment of the suitability of this information. The information is furnished without warranty and any use of this product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. Seradyn, Inc. shall not be held liable for any damage resulting from handling or from contact with the above named product.

Dispose of product in accordance with all applicable Federal, State, and local regulatory guidance.