



M
 Stainless Steel Rotor
 24-Place, 16 ml
 Tube Dimensions:
 18 × 102 mm or
 17 × 120 mm
 Fixed-Angle: 35°
 Maximum Speed: 6,000 rpm
 Rotor Mass: 2.8 kg

Outer Row	RCF (g)	R (cm)
Max.	4,894	12.17
Min.	2,260	7.12
Inner Row	RCF (g)	R (cm)
Max.	3,675	9.14
Min.	1,033	4.07

For use in RC-3,¹ GLC-2B,¹ and GLC-3¹ centrifuges

Catalog No. 33029

Includes:
 M Rotor Tube Holders **00501**
 Rotor Cover Instruction Manual **33032**

TUBES

CAPACITY (ml)		DESCRIPTION	MAX SPEED (rpm)	DIMENSIONS (mm)	TUBE CAT. NO. (Qty/Pkg)	SEALING ASSEMBLY*		ADAPTER REQ'D		NOTES
NOMINAL	FILL					CAT. NO. (Qty/Pkg)	DESCRIPTION	CAT. NO. (Qty/Pkg)	NO. OF PLACES	
17	13	Polyallomer Thin-Walled Tube	6,000	16 × 102	03126 (50)	—	—	—	—	
16	13	Polypropylene Flanged Tube	6,000	18 × 100	03244 (50)	03299 (50)	Polypropylene, Snap-on	—	—	
16	14	Polycarbonate Flanged Tube	6,000	18 × 100	03243 (50)	03269 (50)	Polypropylene, Snap-on	—	—	
15	—	Urinalysis Tube, Conical	—	17 × 120	—	—	—	—	—	Maximum rotor capacity is 16 tubes.
15	12	Corex® Tube	6,000	18 × 102	03286 (25)	—	—	03667 (12)	1	
12	12	Pyrex® Tube	5,000	18 × 102	03109 (50)	—	—	03667 (12)	1	
12	10	Polypropylene Flanged Tube	6,000	16 × 100	03116 (50)	03266 (50)	Polypropylene, Snap-on	—	—	
12	11	Polycarbonate Flanged Tube	6,000	16 × 100	03115 (50)	03266 (50)	Polypropylene, Snap-on	—	—	
10	—	Vacutainer® Tube	—	16 × 100	—	—	—	03667 (12)	1	
10	9	Polyallomer Thin-Walled Flanged Tube	6,000	13 × 100	03124 (50)	—	—	00416 (1)	1	
10	—	Pyrex® Tube	—	13 × 100	—	—	—	00373 (1)	1	
7	—	Vacutainer® Tube	—	13 × 100	—	—	—	00373 (1)	1	
7	6	Polycarbonate Flanged Tube	6,000	13 × 100	03120 (50)	03265 (50)	Polypropylene, Snap-on	00416 (1)	1	
7	6	Polypropylene Flanged Tube	6,000	13 × 100	03121 (50)	03265 (50)	Polypropylene, Snap-on	00416 (1)	1	
5	5	Pyrex® Tube	5,000	12 × 75	03102 (50)	—	—	00376 (1)	1	
4	—	Vacutainer® Tube	—	10.25 × 82	—	—	—	00374 (1)	1	
3	3	Pyrex® Tube	5,000	10 × 75	03100 (50)	—	—	00374 (1)	1	
1.5	—	Microtube	—	—	—	—	—	00376 (1)	1	

⁽¹⁾Instrument no longer available.

*Sealing assembly parts may be available. See section E for availability.